

TEST REPORT



REPORT NUMBER: 102589439COQ-001A
ORIGINAL ISSUE DATE: March 14, 2017

EVALUATION CENTER
Intertek Testing Services NA Ltd.
1500 Brigantine Drive
Coquitlam, BC V3K 7C1
Canada

RENDERED TO

Stella Custom Glass Hardware Inc.
#7 – 3671 Viking Way
Richmond, B.C. V6V 2J5
CANADA

Product Manufacturer: **Stella Custom Glass Hardware Inc.**

Product Type: **Aluminum XXXO Sliding Door**

Product Series: **TS2**

Specification: **AAMA/WDMA/CSA 101/I.S.2/A440-08**
AAMA/WDMA/CSA 101/I.S.2/A440-11
A440S1-09

Primary Designator: **NAFS-08 and NAFS-11**
Class LC – PG35 – Size Tested 6120 x 2781 mm (241 x 109 in) –
Type SD

Secondary Designator: **Positive Design Pressure = 1680 Pa (35.1 psf)**
Negative Design Pressure = 1680 Pa (35.1 psf)
Water Penetration Resistance = 400 Pa (8.4 psf)
Canadian Air Leakage Resistance: 75 Pa = A3; 300 Pa = A2

Test Completion Date: **September 9, 2016**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

1 Table of Contents

1	Table of Contents	2
2	Summary of Results	3
2.1.	NAFS-08 SUMMARY	3
2.2.	NAFS-11 SUMMARY	4
3	Introduction	5
4	Test Samples	5
4.1.	SAMPLE AND ASSEMBLY DESCRIPTION	5
5	Testing and Evaluation Methods.....	10
5.1.	OPERATING FORCE.....	10
5.2.	AIR LEAKAGE RESISTANCE.....	10
5.3.	WATER PENETRATION RESISTANCE.....	10
5.4.	UNIFORM LOAD DEFLECTION.....	10
5.5.	UNIFORM LOAD STRUCTURAL.....	10
5.6.	FORCED ENTRY RESISTANCE.....	11
5.7.	DEGLAZING TEST	11
5.8.	INSECT SCREEN SERVICEABILITY TEST.....	11
5.9.	DEVIATION FROM STANDARD METHOD.....	11
6	Test Apparatus.....	11
7	Testing and Evaluation Methods.....	12
7.1.	OPERATING FORCE.....	12
7.2.	AIR LEAKAGE RESISTANCE.....	12
7.3.	WATER PENETRATION RESISTANCE.....	12
7.4.	UNIFORM LOAD DEFLECTION.....	13
7.5.	UNIFORM LOAD STRUCTURAL.....	13
7.6.	FORCED ENTRY RESISTANCE.....	13
7.7.	DEGLAZING TEST	13
8	Conclusion	14
	APPENDIX A – Drawings	16 Pages
	APPENDIX B – Photograph	13 Pages
	APPENDIX C – Revision Table	1 Page

2 Summary of Results

2.1. NAFS-08 SUMMARY

A summary of results for AAMA/WDMA/CSA 101/I.S.2/A440-08 “Standard/Specification for windows, doors, and unit skylights”, are as indicated in the table below:

Evaluation Property	Result
Operating Force	US – Pass; Can - Pass
Air Leakage Resistance @ 75 Pa (1.6 psf)	US – Pass; Can – A3
Air Leakage Resistance @ 300 Pa (6.4 psf)	US – Pass; Can – A2
Water Penetration Resistance	400 Pa (8.4 psf)
Uniform Load – Deflection	1680 Pa (35.1 psf)
Uniform Load – Structural	2520 Pa (52.7 psf)
Forced Entry Resistance	Gr. 20
Deglazing	Pass

Details of the tested results can be found in Section 7 of this report.

Primary and Secondary Designations are as indicated below:

TS2 Series Aluminum XXXO Sliding Door

Class LC – PG35 – Size Tested 6120 x 2781 mm (241 x 109 in) – Type SD

Secondary Designation

Positive Design Pressure = 1680 Pa (35.1 psf)
Negative Design Pressure = 1680 Pa (35.1 psf)
Water Penetration Resistance = 400 Pa (8.4 psf)
Canadian Air Leakage Resistance: 75 Pa = A3; 300 Pa = A2

2.2. NAFS-11 SUMMARY

A summary of results for AAMA/WDMA/CSA 101/I.S.2/A440-11 “Standard/Specification for windows, doors, and unit skylights”, are as indicated in the table below:

Evaluation Property	Result
Operating Force	US – Pass; Can - Pass
Air Leakage Resistance @ 75 Pa (1.6 psf)	US – Pass; Can – A3
Air Leakage Resistance @ 300 Pa (6.4 psf)	US – Pass; Can – A2
Water Penetration Resistance	400 Pa (8.4 psf)
Uniform Load – Deflection	1680 Pa (35.1 psf)
Uniform Load – Structural	2520 Pa (52.7 psf)
Forced Entry Resistance	Gr. 20
Deglazing	Pass

Details of the tested results can be found in Section 7 of this report.

Primary and Secondary Designations are as indicated below:

TS2 Series Aluminum XXXO Sliding Door

Class LC – PG35 – Size Tested 6120 x 2781 mm (241 x 109 in) – Type SD

Secondary Designation

Positive Design Pressure = 1680 Pa (35.1 psf)
Negative Design Pressure = 1680 Pa (35.1 psf)
Water Penetration Resistance = 400 Pa (8.4 psf)
Canadian Air Leakage Resistance = 75 Pa = A3; 300 Pa = A2

3 Introduction

Intertek Testing Services NA Ltd. (Intertek) has conducted testing for Stella Custom Glass Hardware Inc. (Stella) on a 6120 mm x 2781 mm (240.9" x 109.5") TS2 Series Aluminum XXXO Sliding Door in accordance with:

- AAMA/WDMA/CSA 101/I.S.2/ A440-08 “Standard/Specification for windows, doors, and unit skylights” (NAFS-08)
- AAMA/WDMA/CSA 101/I.S.2/ A440-11 “Standard/Specification for windows, doors, and unit skylights” (NAFS-11)
- A440S1-09 “Canadian Supplement to AAMA/WDMA/CSA 101/I.S.2/A440, NAFS – North American Fenestration Standard/Specification for windows, doors, and skylights” (A440S1)

This evaluation began on June 8, 2016 and completed on September 9, 2016.

4 Test Samples

4.1. SAMPLE AND ASSEMBLY DESCRIPTION

Type (general)	<ul style="list-style-type: none"> • Aluminum XXXO Sliding Door
Series	<ul style="list-style-type: none"> • TS2
Test Fixture	<ul style="list-style-type: none"> • Test Buck: 2x8 LVL (sill and jambs) and 4x8 LVL (head) box w/ 2x14 LVL cladding, butt joints secured with 3x #12 x 3" deck screws. The 2x12 clad was also butt jointed together with 6x #12 x 3" deck screws and secured to the 2x8 with #12 x 3" flat head screws used in pairs, at 305 mm (12") oc. • The test buck was built with a rough opening approximately 1/4" larger than the sample size in width and height. Backer rod and silicone are used to seal the entire perimeter of the rough opening on the interior and exterior sides. • Specimen to Buck: <ul style="list-style-type: none"> • The sill was secured with the use of a 3/4" x 3/4" x 1/8" thick aluminium angle. The aluminium angle was used along the full length of the interior side of the sill. Secured to the test buck with #8 x 1" self-tapping flat-head screws spaced 305 mm (12") o.c., and secured to the sill with #8 x 3/4" self-tapping flat-head screws spaced 305 mm (12") o.c. • Each of the three head tracks were secured into the test buck by #8 x #12 x 3" pan head screws w/ washers, spaced 152 mm (6") o.c.. • Each jamb was secured to the test buck with the use of #10 x 2" flat-head screws. The screws were use in groups of 6, in three places along each jamb spaced approximately 1092 mm (43") o.c., and approximately 305 mm (12") from the ends of the jambs. • A 5" x 8" aluminum mullion assembly is used along the length of one jamb, secured with the use of a 2" x 3" x 1/4" angle, and a 5" x 1/4" aluminum plate. The angle is secured to the mullion with #10 x 1" pan head screws used in groups of two, approximately 305 mm (12") o.c. • The angle was riveted into the plate, and the plate was secured to test buck with #10 x 1" pan head screws used in groups of two (one in to the 2x8 and one in to the 2x14 buck), approximately 305 mm (12") o.c. • Silicone was used to seal all screw heads, and joints of the test buck.

Size	<ul style="list-style-type: none"> Overall Size: <ul style="list-style-type: none"> Width: 6120 mm (240.9") Height: 2400 mm (109.5")
Frame	<ul style="list-style-type: none"> Material: Aluminum Reinforcement: None The sill assembly included three black PVC tracks, full length for the middle track and one each under the two fixed slabs the length of the slab. Three 7/16" holes are present through the top of the middle track, approximately 7" from either end of track and at the astragal between the two operable doors. Each track under the fixed unit has two lengths of 1-1/8" x 3/4" x 25" black PVC solid rectangle stock, butted to either end of the tracks. Where a track is not used, a snap-in aluminium sill threshold is used to cover the sill cavity. The head assembly includes three aluminum track profiles, with clip-on aluminum profiles on the interior and exterior face, as well as black PVC profiles between the track assemblies. Silicone was used to seal each joining profile. The interior track had a snap-in cover clip along the entire length, and the exterior track had a cover clip used where the fixed slabs were not present. Each of the jamb profiles are the same, however the mullion side jamb has each of the three pockets covered with a snap-in cover clip, while the non-mullion side had a fixed slab inserted into the exterior pocket instead of the cover clip. Each cover clip has a 64 mm (2-1/2") diameter 25 mm (1") piece of foam backer rod used to fill the gap between the end of the cover clip and the jamb. Corners: Butt Joined. Secured from the verticals in to the horizontals with the use of 6x #10 x 1-1/4" pan head self-tapping screws. Three XPS foam blocks were used at each corner of the horizontals butted up against the jambs and sealed with silicone.
Mullion	<ul style="list-style-type: none"> An aluminum curtain wall mullion assembly is used on the exterior side, along the length of the left jamb. The mullion profile was not provided by Stella nor did it have any effect on the testing. The mullion was used as demonstrative purposes only. The mullion has overall dimensions of 5" x 8", consisting of a 5"x5" aluminum box, two thermal struts connecting the box to another aluminum profile with two T shaped EPDM gaskets inserted into kerfs, which also act as chases for bolts (Figure 3 in Appendix B). An aluminum plate is secured into this profile and there is an aluminum cap which snaps in over the plate. The plate is bolted to the aluminum profile with the use of 1/4" x 3/4" bolts, used in pairs, spaced 152 mm (6") o.c. The mullion has a black PVC interlock profile with an aluminum flat stock set inside it, secured along the length of the mullion on the interior side to engage with the interlock of the adjacent fixed panel. The interlock is secured with #10 x 1-1/2" flat head self-tapping screws, spaced 102 mm (4") o.c.
Operable Sash (3x)	<ul style="list-style-type: none"> Material: Aluminum Corners: Mitre cut and joined with the use of a shear block. Shear block is secured to each the stile and rail from the glass opening side with the use of 4x #10 x 1-1/2" flat-head screws on each side. Each screw head is sealed with silicone. Additional 1x #10 x 1-1/2" flat-head screws are used from the outside of the slab perimeter through the rail and in to the horizontal of the shear block. First Panel Size: <ul style="list-style-type: none"> Width: 1571 mm (61.9") Height: 2641 mm (104.0") Second Panel Size: <ul style="list-style-type: none"> Width: 1523 mm (60.0") Height: 2641 mm (104.0")

	<ul style="list-style-type: none"> • Third Panel Size: <ul style="list-style-type: none"> • Width: 1523 mm (60.0") • Height: 2641 mm (104.0") • A black PVC interlock profile is used along the stile that meets the fixed sash, secured with #8 x 1" self-tapping pan head screws, spaced approximately 305 mm (12") o.c. The length of the interlock is also adhered to the length of the aluminum with two lengths of black foam double sided tape, 1/4" wide. • The top of the exposed edge of the interlock stile has a 1/2" thick plate of UHMW plastic used, 2-1/4" x 2-3/4", secured with 4x #10 x 1-1/4" self-tapping pan head screws. • The bottom of the exposed edge of the interlock stile has a 1/4" thick aluminum plate used with overall dimensions of 2-1/4" x 2-3/4" cut with a notch to fit over the track profile. Secured with 2x #10 x 1-1/2" self-tapping flat head screws. 4x strips of mohair weather-stripping are adhered to the plate, oriented vertically, 2x on the outside, and 2x sandwiched between the plate and the stile. • An aluminum astragal profile is used along the locking stile of the secondary panel. Secured to the edge of the stile with 8x #10 x 1" flat head screws. The astragal is sealed to the sash along the exterior edge with silicone • The operable slab with the mullion has an additional interlock profile with the use of an aluminium flat stock set inside it used along the jamb side to engage with the interlock of the mullion. Secured along the stile of the sash with #10 x 1-1/2" flat head self-tapping screws, spaced 102 mm (4") o.c. The length of the interlock is also adhered to the length of the aluminum with two lengths of black foam double sided tape, 1/4" wide. • The top of the exposed edge of the interlock stile has a 1/4" thick aluminium plate used, cut to be inserted and to fill the gap of the track profile. The top section that is inserted into the track has a 1/4" wide plastic secured to the aluminum, and two full perimeters of a mohair weather-stripping with centre fin is adhered to the aluminium and plastic. The aluminium plate is secured with 2x #10 x 1-1/4" self-tapping pan head screws.
Fixed Sash	<ul style="list-style-type: none"> • Material: Aluminum • Corners: Mitre cut and joined with the use of a shear block. Shear block is secured to each the stile and rail from the glass opening side with the use of 4x #10 x 1-1/2" flat-head screws on each side. Each screw head is sealed with silicone. Additional 2x #10 x 1-1/2" flat-head screws are used from the outside of the slab perimeter through the rail and in to the horizontal of the shear block. • Panel Size: <ul style="list-style-type: none"> • Width: 1571 mm (61.9") • Height: 2641 mm (104.0") • A black PVC interlock profile is used along the stile that meets the operable sash, secured with #8 x 1" self-tapping pan head screws, spaced approximately 305 mm (12") o.c. with a black PVC cap over top of the screws. The length of the interlock is also adhered to the length of the aluminum with two lengths of black foam double sided tape, 1/4" wide. • The sash on the non-mullion side is secured in place through the jamb side stile and in to the jamb and test buck with 2x #12 x 3" screws, centered approximately 406 mm (16") from the top and bottom of the sash.
Lock and Rollers	<ul style="list-style-type: none"> • Locking plate with deadbolt activator on the primary panel secured to the locking stile with 3x #8 x 1" screws. Locking point is centered 1270 mm (50") from the bottom of the slab. • A handle is used on each operable slab, secured from the interior to itself on the exterior. The bottom of the handle is positioned 940 mm (37") from the bottom of the slab

	<ul style="list-style-type: none"> Each operable slab and the fixed on the mullion side have two roller assemblies attached to the top rail, each assembly consisting of 4 rollers. A 1/4" thick aluminum plate is slotted into the top rail profile, and secured with 1x #10 x 1-1/2" screw. The plate has a hole that the roller assembly bolt is secured to, and the top rail thermal break is drilled to allow the bolt to pass through.
Drainage	<ul style="list-style-type: none"> The aluminum sill has 7x drains through two locations of the sill profile, through the exterior face and through the first tower closest to the exterior. The drain through the exterior face is approximately 1" wide, 1/4" tall fit with a weep hole cover which is sealed in place with silicone. The drain through the tower is three 5/16" holes adjacent to one another. From the mullion side edge of the sill, the drains are centered approximately 254 mm (10"), 965 mm (38"), 1994 mm (78-1/2"), 2934 mm (115-1/2"), 3874 mm (152-1/2"), 4814 mm (189-1/2"), 5702 mm (224-1/2"). The PVC track under the fixed sashes has 1" long notches through the vertical feet and part of the horizontal edge of the exterior side. The drain notches are in two locations, centered 305 mm (12") from the jamb and 102 mm (4") from the interlock. An additional notch is used at the mid-point, only through the vertical, not the horizontal. The track for the operable sashes has notches through the feet, holes through the verticals on top of the horizontal and holes down through the exterior side of the horizontal. <ul style="list-style-type: none"> The notches through the interior side foot are 1" x 1/4", and centered approximately 584 mm (23"), 1435 mm (56-1/2"), 2184 mm (86") and 2934 mm (115-1/2") from the mullion side end of the track, and 483 mm (19"), 1200 mm (47-1/4"), 2019 mm (79-1/2") and 2864 mm (112-3/4") from the non-mullion side end of the track. The notches through the exterior side foot are 1" x 1/4", and centered approximately 178 mm (7"), 1016 mm (40"), 1835 mm (72-1/4") and 2559 mm (100-3/4") from the mullion side end of the track, and 108 mm (4-1/4"), 851 mm (33-1/2"), 1594 mm (62-3/4") and 2451 mm (96-1/2") from the non-mullion side end of the track The holes through the interior side vertical on top of the horizontal are 5/16" diameter. Centered 749 mm (29-1/2") and 2248 mm (88-1/2") from the mullion side end of the track, and 635 mm (25") and 2292 mm (90-1/4") from the non-mullion side end of the track. The holes through the exterior side vertical on top of the horizontal are 5/16" diameter. Centered 108 mm (4-1/4") and 1549 mm (61") from the mullion side end of the track, and 1568 mm (61-3/4") and 2972 mm (117") from the non-mullion side end of the track. The holes through the exterior side horizontal are 1/4" diameter. Centered 921 mm (36-1/4") and 2457 mm (96-3/4") from the mullion side end of the track, and 114 mm (4-1/2"), 851 mm (33-1/2") and 2610 mm (102-3/4") from the non-mullion side end of the track.
Weather-stripping	<ul style="list-style-type: none"> Each sash pocket of the frame has 2x full perimeters of weather-stripping, one interior facing and one exterior facing so they both contact the sash. <ul style="list-style-type: none"> Along the jambs the weather-stripping does not have a fin (Figure 22 in Appendix B). Along the sill, pile weather-stripping with a fin (Figure 23 in Appendix B). Except a rubber fin seal (Figure 24 in Appendix B), is used on the exterior side of the middle, operable sash pocket, as well as along the length of the fixed slab on the mullion side. The sill has additional pile weather-stripping along the PVC tracks (Figure 23 in Appendix B).

	<ul style="list-style-type: none"> • The head assembly has pile weather-stripping on the snap-on aluminum and PVC carriers. The exterior side aluminum has no fin (Figure 25 in Appendix B). The interior side aluminum has a center fin (Figure 26 in Appendix B), and the pvc carrier has two different piles, each with a fin (Figure 27 in Appendix B). Except a rubber fin seal (Figure 24 in Appendix B) is used on the exterior side of the middle, operable sash pocket, as well as along only the length of the fixed slab on the mullion side. • Each sash has kerf inserted pile weather-stripping along the full length of the bottom rail, along the exterior and also along the interior side (Figure 28 in Appendix B). • Each sash has a piece of 3/8" black closed cell foam, the width of the sash, cut on a 45° angle on top of the sash interlock stile, positioned to deflect water to the exterior (Figure 21 in Appendix B). • The operable sashes with the aluminum plate on the bottom of the interlock profile each have four lengths of adhesive backed pile weather-stripping without a fin (Figure 29 in Appendix B). • Top of sash fin seal (Figure 24 in Appendix B). • Each interlock has three lengths of weather-stripping. The exterior face has two lengths of pile with center fin (Figure 30 in Appendix B), and inside the interlock is a hollow rubber bulb seal (Figure 9 in Appendix B). • At the top of the mullion, above where the interlock ends, there is a vertical 6" length of 3/8" x 2" closed cell black foam gasket adhered to the aluminum. On the other side of the same joint, there are two horizontal 6" lengths of 3/8" x 2" closed cell black foam gasket adhered to the snap-on aluminum profile along the exterior of the head (Figure 20 in Appendix B). • The primary sash has a foam filled vinyl wrapped kerf inserted weather-stripping along the exterior side of the locking stile (Figure 31 in Appendix B). • The secondary sash has a foam kerf inserted weather-stripping along the interior side of the locking stile (Figure 32 in Appendix B). • The astragal along the secondary sash has a pile weather-stripping with center fin and hollow bulb weather-stripping (Figure 10 in Appendix B).
<p>Glazing (4x)</p>	<ul style="list-style-type: none"> • IGU specification: <ul style="list-style-type: none"> • 6 mm / 6 mm clear tempered with a 12 mm (1/2") aluminum spacer bar with loose fill desiccant, sealed together using hot melt butyl. • Overall thickness, 25 mm (1") • Laid-in, interior dry glazed on top of an EPDM gasket, glazing stop on interior side with an EPDM gasket (Figure 33 in Appendix B). All gasket corners sealed with silicone. • The entire perimeter of the glass unit is sealed in the setting block cavity with the use of a backer rod and silicone. • Glazing Blocks: 2x 5 mm (3/16") thick setting blocks, 25 mm (1") wide, 152 mm (6") long under the glass unit, centered approximately 178 mm (7") from either edge of glass.
<p>Drawings</p>	<ul style="list-style-type: none"> • Drawing package supplied by Stella can be found in Appendix A.

5 Testing and Evaluation Methods

5.1. OPERATING FORCE

The Operating Force test was performed on the sash and latch in accordance with ASTM 2068. The forces required initiate motion of the operable panel from both the fully open and fully closed positions, as well as the force required to maintain motion to the opposite limits of travel, were measured. The forces required to open and close the latches were also recorded.

5.2. AIR LEAKAGE RESISTANCE

The Air Leakage Resistance test was performed in accordance with ASTM E283-04(2012), *“Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen”*. Air infiltration and exfiltration tests were performed using test pressures of 75 Pa (1.57 psf) and 300 Pa (6.28 psf). The maximum air leakage rate was calculated and compared to the allowable air leakage.

5.3. WATER PENETRATION RESISTANCE

A four-cycle Water Penetration Resistance test was performed in accordance with ASTM E547-00(2016) *“Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Cyclic Air Pressure Difference”* (ASTM E547). The test was performed using the specified pressure differential and a water spray rate of at least 204 L/m² per hour (5.0 U.S. gal/ft² per hour). Each cycle consisted of five minutes with the pressure applied and one minute with the pressure released, during which the water spray was continuously applied.

5.4. UNIFORM LOAD DEFLECTION

The Uniform Load Deflection tests were conducted in accordance with ASTM E330-02(2010) *“Standard Test Method for Structural Performance of Exterior Windows, Skylights, Doors and Curtain Walls by Uniform Static Air Pressure Difference”* (ASTM E330), Procedure A. The tests were performed in both the positive and negative directions. After a 10 second preload (50% of the test load), followed by 1 minute with the pressure released, the tests were conducted at the specified test pressure for a period of 10 seconds. Deflections were measured at the mid-span and at the ends. The end deflections were averaged and subtracted from the mid-span deflection (to eliminate deflections caused by movement at the ends of the structural supporting members). Polyethylene film was used during the positive wind pressure sequences.

5.5. UNIFORM LOAD STRUCTURAL

The Uniform Load Structural tests were conducted in accordance with ASTM E330-02(2010) *“Standard Test Method for Structural Performance of Exterior Windows, Skylights, Doors and Curtain Walls by Uniform Static Air Pressure Difference”* (ASTM E330), Procedure A. After a 10 second preload (50% of test load), followed by 1 minute with the pressure released, the sample was subjected to a Uniform Load Structural test using a specified test pressure for a time of 10 seconds. The test was performed in both the positive and negative directions. After the test loads were released, the permanent deflections were recorded and the specimen was inspected for failure or permanent deformation of any part of the system that would cause any operational malfunction. Polyethylene film was used during the positive wind pressure sequences.

5.6. FORCED ENTRY RESISTANCE

The Forced-entry Resistance Test was conducted in accordance with ASTM F842-14 “Standard Test Methods for Measuring the Forced Entry Resistance of Sliding Door Assemblies, Excluding Glazing Impact”. This included the Disassembly, Sash Manipulation, Lock Hardware Manipulation, and Assembly Tests.

5.7. DEGLAZING TEST

The deglazing test was conducted in accordance with Section 5.3.6.3 of NAFS-08 and Section 9.3.6.3 of NAFS-11. After the test loads were removed, the specimen was inspected for any damage that would inhibit the normal operation of the system.

5.8. INSECT SCREEN SERVICEABILITY TEST

Testing not applicable.

5.9. DEVIATION FROM STANDARD METHOD

There were no noted deviations from the test standards used in the evaluation reported herein.

6 Test Apparatus

Equipment used during testing is listed as follows:

Test	Equipment	Intertek ID#	
Air Leakage Resistance, Water Penetration Resistance, and Uniform Load Deflection / Structural	Fenestration Testing Control Unit	60650	
	Water spray assembly	60651	
		60652	
		60653	
	20" Line Gauge	64919	
		64920	
		64921	
	Forced-entry Resistance	5000 lbs Load Cell	P60691
		1000 lbs Load Cell	P60688
P60689			
Deglazing	200 lbs Load Cell	P60687	
	1000 lbs Load Cell	P60688	
	Mitutoyo Digital Deflection Gauge	P60175	

7 Testing and Evaluation Methods

7.1. OPERATING FORCE

The forces required to open and close the sash were measured as follows:

Initiate Opening:	129.6 N (29.1 lbs)	Initiate Closing:	128.2 N (28.8 lbs)
Maintain Opening:	69.0 N (15.5 lbs)	Maintain Closing:	78.0 N (17.5 lbs)
Latch Opening:	N/A	Latch Closing:	N/A
Maximum allowable force to initiate motion:	135 N (30 lbs)		
Maximum allowable force to maintain motion:	90 N (20 lbs)		
Maximum allowable force to open and close latch:	100 N (22 lbs)		

The tested specimen **MET** the performance requirements of NAFS-08, NAFS-11 and A440S1 for Operating Force.

7.2. AIR LEAKAGE RESISTANCE

Air test data is indicated in the following table:

Overall Assembly (75 Pa)	
Area:	17.02 m ² , 183.20 ft ²
Infiltration rate:	0.34 L/s*m ² , 0.07 cfm/ft ²
Exfiltration rate:	0.35 L/s*m ² , 0.07 cfm/ft ²
Overall Assembly (300 Pa)	
Area:	17.02 m ² , 183.20 ft ²
Infiltration rate:	1.11 L/s*m ² , 0.22 cfm/ft ²
Exfiltration rate:	1.07 L/s*m ² , 0.21 cfm/ft ²
Allowable Leakage Rates	
Maximum allowable air leakage rate (US):	1.5 L/s*m ² , 0.3 cfm/ft ²
Maximum allowable air leakage rate (CAN – A3):	0.5 L/s*m ² , 0.1 cfm/ft ²
Maximum allowable air leakage rate (CAN – A2):	1.5 L/s*m ² , 0.3 cfm/ft ²

The overall system **met** the US performance requirements as well as the **A3 (75 Pa)** and **A2 (300 Pa)** Canadian performance requirements when evaluated under NAFS-08, NAFS-11 and A440S1.

7.3. WATER PENETRATION RESISTANCE

During the 24-minute test period, using a pressure differential of 400 Pa (8.4 psf), there was no water leakage observed. The system **met** the **(Can) PG55** Water Penetration Resistance performance requirements under NAFS-08, NAFS-11 and A440S1.

7.4. UNIFORM LOAD DEFLECTION

Uniform Load Deflection data:

Test Pressure, Pa (psf)	Deflection Measurements, mm (in.)				Compliance
	Positive		Negative		
	Deflection	Residual	Deflection	Residual	
1680 (35.1)	24.42 (0.96)	1.14 (0.04)	23.27 (0.92)	1.42 (0.06)	Pass DP35
Astragal span, L = 2490 mm (98.03")			Deflection limit, L/175 = N/A		

After the test loads were released, the specimen was inspected and there was found to be no failure or permanent deformation of any part of the system that would cause any operational malfunction. The system **met** the **DP35** Uniform Load Deflection performance requirements under NAFS-08 and NAFS-11.

7.5. UNIFORM LOAD STRUCTURAL

Uniform Load Structural data:

Test Pressure, Pa (psf)	Residual Deflection Measurements, mm (in.)		Compliance
	Positive	Negative	
2520 (52.6)	5.92 (0.23)	4.62 (0.18)	Pass DP35
Astragal span, L = 2290 mm (90.16")		Residual deflection limit, L*0.4% = 9.16 mm (0.36")	

After the test loads were released, the specimen was inspected and there was found to be no failure or permanent deformation of any part of the system that would cause any operational malfunction. The system **met** the overall **DP35** Uniform Load Structural performance requirements under NAFS-08 and NAFS-11.

7.6. FORCED ENTRY RESISTANCE

Attempts to gain entry by opening the glazing panel, in accordance with the Disassembly and Sash Manipulation tests for a Type A assembly, were unsuccessful. The system met the **Grade 20** Forced-entry Resistance performance requirements of NAFS-08 and NAFS-11.

7.7. DEGLAZING TEST


	Vertical (Interlock Stile)	Horizontal (Bottom Rail)
Load, N	320	230
Deflection, mm	1.44	0.83
Allowable, mm	9 mm	

After the test loads were removed, the specimen was inspected for any damage that would inhibit the normal operation of the system. The tested specimen **met** the performance requirements of NAFS-08 and NAFS-11.

8 Conclusion

The TS2 Series Aluminum XXXO Sliding Door tested and described herein achieved the overall performance requirements for Class LC – PG35 when tested in accordance with NAFS-08, NAFS-11 and A440S1.

INTERTEK TESTING SERVICES NA LTD.

Reported by: 

Jason Komorski
Technician – Building Products

Reviewed by: 

Riccardo DeSantis
Manager – Building Products

APPENDIX A
Drawings – 16 Pages

STELLA TS2 INTERTEK

RICHMOND, BC

TOP HUNG SLIDING DOORS AND TRANSOM

GENERAL NOTES:

1. WHERE SHOWN OR REFERRED TO BY A DIMENSION LINE, ALL DIMENSIONS ARE TO FACE UNLESS SPECIFICALLY NOTED OTHERWISE. DIMENSIONS TO FACE SHALL BE INDICATED BY DIMENSION LINES WITH ARROWS POINTING TO THE ACTUAL ARCHITECTURAL FINISH SURFACE. DIMENSIONS TO CENTER SHALL BE INDICATED BY DIMENSION LINES WITH ARROWS POINTING TO THE CENTER LINE OF THE MEMBER OR FINISH SURFACE.
2. GENERAL CONTRACTOR MUST PROVIDE ADEQUATE CLEARANCE TO THE GLASS AND FINISH MATERIALS TO BE INSTALLED. ALL DIMENSIONS SHALL BE TO FACE UNLESS SPECIFICALLY NOTED OTHERWISE. DIMENSIONS TO FACE SHALL BE INDICATED BY DIMENSION LINES WITH ARROWS POINTING TO THE ACTUAL ARCHITECTURAL FINISH SURFACE. DIMENSIONS TO CENTER SHALL BE INDICATED BY DIMENSION LINES WITH ARROWS POINTING TO THE CENTER LINE OF THE MEMBER OR FINISH SURFACE.
3. THE GLASS SHALL BE SUPPLIED BY THE GENERAL CONTRACTOR. THE GLASS SHALL BE SUPPLIED TO THE SITE IN A SAFE AND SOUND MANNER. THE GLASS SHALL BE PROTECTED FROM DAMAGE AND THE GLASS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.
4. STELLA WILL BE RESPONSIBLE FOR THE PROVISION OF THE GLASS AND FINISH MATERIALS TO BE INSTALLED. STELLA WILL BE RESPONSIBLE FOR THE PROVISION OF THE GLASS AND FINISH MATERIALS TO BE INSTALLED.
5. NO MATERIAL SHALL BE USED FOR THE GLASS AND FINISH MATERIALS TO BE INSTALLED.
6. ANY REVISIONS TO THE DRAWINGS SHALL BE MADE TO THE DRAWINGS BY THE GENERAL CONTRACTOR. STELLA WILL BE RESPONSIBLE FOR THE PROVISION OF THE GLASS AND FINISH MATERIALS TO BE INSTALLED.
7. APPROVED BY: [Signature]

MATERIALS:

GLASS: [Details]

FINISH: [Details]

ADDITIONAL NOTES:

FOR GLASS SIZES REFER TO PAGE 200

SYMBOLS & ABBREVIATIONS:

SECTION OR ELEVATION (DIRECTION OF VIEW): [Symbol]

SECTION OR ELEVATION (DIRECTION OF VIEW): [Symbol]


SECTION OR ELEVATION (DIRECTION OF VIEW): [Symbol]


PRINT RECORD

NO.	DATE	DESCRIPTION	BY	CHECKED
1	2017.03.14	ISSUED FOR FABRICATION	[Signature]	[Signature]

ISSUED FOR FABRICATION








SECTION THRU HEAD POCKET PANEL
 Scale: 200
 200
 Scale: 200

<p>300</p> <p>V4394</p> <p>TS203</p> <p>GENERAL APPT 7 HEAD DETAILS</p> <p>TS5 ALUMINUM SLIDING DOORS P13-X30</p> <p>Unit 7, 3071 Village Way Richmond, BC, Canada</p> <p>DATE: 10-10-17 LIT 200 1:4=17</p> <p>NOTE: - ALL DIMENSIONS TO BE VERIFIED ON SITE - CUSTOMER RESPONSIBLE FOR PROVISION OF PROPER OPENING FRAME DIMENSIONS - INSTALLATION TO BE CARRIED OUT BY SKILLED APPROVED INSTALLERS - METRIC DIMENSIONS TAKE PRECEDENCE</p>									
<p>ISSUED FOR FABRICATION</p>									





**SECTION THRU SILL
POCKET PANEL**
Scale:



102589439COQ-001A
102589439COQ-001A
www.stellahardware.com


NOTE:

- ALL DIMENSIONS TO BE VERIFIED ON SITE
- CUSTOMER RESPONSIBLE FOR PROVISION OF ROUGH OPENING OR FRAME DIMENSIONS
- INSTALLATION TO BE CARRIED OUT BY STELLA APPROVED INSTALLERS
- METRIC DIMENSIONS TAKE PRECEDENCE


Project	Date	Checked	Rev.	Approved	Doc.


ISSUED FOR FABRICATION

<p>Material</p> <p>TS2 ALUMINUM SLIDING DOORS PXX-XXD</p>	<p>Scale</p> <p>1:1</p> <p>Frame height</p> <p>200 (12-17)</p>
<p>Company name</p> <p>Unit 7- 3671 Viking Way Richmond, BC, CANADA</p>	
<p>Manufacturer</p> <p>GENERAL ALBERT SILL DETAILS</p>	
<p>Product name and tag</p> <p>TS203</p>	
<p>Reference</p> <p>V4394</p>	
<p>Reference</p> <p>301</p>	



<p>302</p> <p>V1391</p> <p>T2203</p> <p>GENERAL AREA 7</p> <p>DETAILS</p> <p>2x6 ALUMINUM</p> <p>SLIDING DOORS</p> <p>XXX-XXX</p> <p>1870 BULLOCK RD. CANADA</p> <p>UNIT 7, 3071 VING RD</p> <p>1870 BULLOCK RD. CANADA</p>			
<p>ISSUED FOR FABRICATION</p>		<p>DATE: 03/14/17</p> <p>BY: [Signature]</p>	
<p>NOTE:</p> <p>- ALL DIMENSIONS TO BE VERIFIED ON SITE</p> <p>- CUSTOMER RESPONSIBLE FOR PROVIDING</p> <p>OF ROUGH OPENING ON FRAMES</p> <p>DIMENSIONS</p> <p>- INSTALLATION TO BE CARRIED OUT BY</p> <p>SEAL APPLICATIONS</p> <p>- WITH 3/8" BRUSHING TAP PROVISIONS</p>			
<p>stella</p>			





stella
201-431-8888 • 10000 16th Street • Richmond, BC, Canada
100-1001-1000 • www.stellahardware.com

REVISIONS

Design	Date	Checked	Rev.	Approved	By

NOTE:
- ALL DIMENSIONS TO BE VERIFIED ON SITE.
- CUSTOMER RESPONSIBLE FOR PROVISION OF ROUGH OPENING OR FRAME DIMENSIONS.
- INSTALLATION TO BE CARRIED OUT BY STELLA APPROVED INSTALLERS.
- METRIC DIMENSIONS TAKE PRECEDENCE.

PROJECT

Project No.	
Client	
Address	

UNIT 7-3671 Viking Way
Richmond, BC, CANADA

PRODUCT TS2 ALUMINUM SLIDING DOORS PEX-XXD


PROJECT TITLE GENERAL ARR'GT HEAD DETAILS

PROJECT NO. TS203

DATE V4394

REVISED 304

ISSUED FOR FABRICATION



SECTION THRU SILL
FIXED PANEL
200
Scale:

stella
102589439COQ-001A
www.stellahardware.com

Order #	Rev.	Created	Iss.	Approved	By

NOTE:
- ALL DIMENSIONS TO BE VERIFIED ON SITE
- CUSTOMER RESPONSIBLE FOR PROVISION OF ROUGH OPENING OR FRAME DIMENSIONS
- INSTALLATION TO BE CARRIED OUT BY STELLA APPROVED INSTALLERS
- METRIC DIMENSIONS TAKE PRECEDENCE

NO.	REVISION	DATE

Project: **ALB** Rev: **1.01**
Project Number: **200** Date: **14-17**

Address or Office:
Unit 7-3671 Viking Way
Richmond, BC, CANADA

Product: **TS2 ALUMINUM SLIDING DOORS PXX-XX0**

Category: **GENERAL ALUMINUM SILL DETAILS**


Project Name/ID: **TS203**

Customer: **V4394**


Manufacturer: **305**

ISSUED FOR FABRICATION


Mullion assembly not provided from Stella



ISSUED FOR FABRICATION



Mullion assembly not provided from Stella



SECTION THRU STILES
 200 Scale
 CLOSED

ISSUED FOR FABRICATION



stella
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890

NOTE:
 ALL DIMENSIONS TO BE VERIFIED ON SITE
 - CUSTOMER RESPONSIBLE FOR PROVISION
 OF PROUDING OPENING IN WALL
 - DIMENSION TO BE CHECKED OUT BY
 STELLA REPRESENTATIVE
 - INTENT DIMENSIONS HAVE PRECEDENCE

**TS2 ALUMINUM
 SLIDING DOORS
 STILES
 DETAILS
 308-X10**

**GENERAL ARCHITECT
 STILES
 DETAILS
 TS203
 V4394
 308**

1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890
 1234567890



NOTE:
 ALL DIMENSIONS TO BE VERIFIED ON SITE.
 CUSTOMER RESPONSIBLE FOR PROVISION OF PROTECTIVE FILM IN FRAME ASSEMBLY.
 INSTALLATION TO BE CARRIED OUT BY A QUALIFIED GLAZING CONTRACTOR.
 ALL DIMENSIONS TO BE VERIFIED ON SITE.

1047 7th Street, Suite 100
 Richmond, BC, Canada


**TS2 ANTI-TURN SLIDING DOORS
 STILES
 DETAILS
 PXX-KXD**

GENERAL ALERT 'T'
 STILES
 DETAILS
 TS203

V4394

309

ISSUED FOR FABRICATION



DATE	REV	BY	CHKD	APP

NOTE
ALL DIMENSIONS TO BE REFERENCED TO CENTERLINE UNLESS OTHERWISE SPECIFIED.
DIMENSIONS TO BE CONFIRMED ON-IT BY THE PERSONNEL AT THE FABRICATION SITE.
REVISIONS TO BE CONFIRMED BY THE PERSONNEL AT THE FABRICATION SITE.

DATE	REV	BY	CHKD	APP
28	1.0			

PROJECT: 310
DATE: 1/28/17

102589439 COQ-001A

431
1.0

310

102589439 COQ-001A

**TS2 ATTORNEY
SLIDING DOORS
ENV-KO**

GENERAL ARRANGEMENT
JAMB
DETAILS

TS203


V4394

310


stella
Stella Custom Glass Hardware Inc.
2001-2005, 2011, 2012, 2013, 2014, 2015, 2016
102589439 COQ-001A
1/28/17

ISSUED FOR FABRICATION


STELLA EXTRUSIONS



Common Stile/Rail Assembly




Common Rail/Lock Assembly



TS2 Head Track




TS2 - Triple Track Frame - Jamb




TS2 - Triple Track Frame - Sill



TS2 Cover clip



TS2 Sill Threshold



TS2 Head Side Cover









Astragal T



Common Glazing Stop

BILL OF MATERIALS

	<p>Hardware</p> <p>Stella TS1-A01 Top Wheel Guide - Top Rail Black (TS1 bolt modified to 80mm)</p> <p>Stella TS1-FP1- Flush Pull Handles - brushed stainless steel</p>
	<p>PVC Extrusions</p> <p>EX047- Head partition, Black PVC</p> <p>EX046- Sill Runner, Black</p> <p>EX034- Interlock base / EX048 Interlock cover Bulb seal and mohair</p>
	<p>Gaskets, Mohair, Weather stripping</p> <p>EX049- T-Seal, Santoprene-Polyethelane Co-extrusion- Black</p> <p>EC3G-GASKET-INT-EPDM- Backer gasket</p> <p>EC3G-GASKET-EXT-EPDM Wedge gasket</p> <p>DS-420-BL Weatherseal - Door Panels - kerf-in - black</p> <p>DS-426-BL Weatherseal - Door Panels - kerf-in - black</p> <p>DS7535-187G- Weather-stripping - Frame - 0.27in back w/ 5/16" with fin - grey</p> <p>DS7630-187G Weather-stripping - Interlock Stile - 0.187in back w/ 1/4" fin - grey</p> <p>DSP-108-50-BL- Pile Seal - Bottom Rail - kerf-in - 1/2" (13mm) - black</p> <p>DST-17-BL- Bulb Seal - Astragal - 6 mm - black</p> <p>2625- Bulb Seal, Black, Polychlor</p>

	<p>Fasteners</p> <p>M10 x 1.5 x 80mm SocketHead Cap Screw M10 Washer machined-Top Roller Bolt</p> <p>12x3 PH-SMS Screw / #12 washer- Mounting Header</p> <p>10 x 2 FH-SMS-Screw - Mounting Jamb</p> <p>12 x 1.5 FH-High Tensile Zinc Plated Steel Screw - Panel Assembly</p> <p>10 x 1.25 PH-SD-TEK Screw - Frame Assembly - Jamb to Sill, Jamb to Header Interlock to panel</p> <p>10 x 0.75 PH-SD-TEK Screw - Bumper screw</p>
	<p>Locks and cylinders</p> <p>MS-1805OS-450-628 Adams rite 1 1/2" Back set Hook lock</p> <p>M-100-SC-26D-ARA2 Mortise cylinder</p> <p>M-100T-26D-AR Thumb turn</p>
	<p>Rubber stops</p> <p>TS1-124 Rubber bumper stops for Jamb</p> <p>KTD-123B Rubber bumper spacer</p>

APPENDIX B
Photograph – 13 Pages



Figure 1 - XXXO Sliding Door – Exterior side
*Note – Picture taken during air leakage test, with poly bag in place.




Figure 2 - 5" x 8" Mullion Section
**Section not supplied by Stella*




Figure 3 - 5" x 8" Mullion gasket
**Section not supplied by Stella*




Figure 4 - Jamb assembly profile



Figure 5 – Sill assembly profiles




Figure 6 – One head track profile



Figure 7 – Common rail/stile sash profile



Figure 8 – Track profile



Figure 9 – Interlock profile




Figure 10 – Astragal profile




Figure 11 – Frame filler cap profile



Figure 12 – Corner key




Figure 13 – Drainage path



Figure 14 – Weep hole cover with silicone




Figure 15 – Blocks attached to sash tops



Figure 16 – Weather-stripping around aluminum profile




Figure 17 – Weather-stripping around aluminum profile



Figure 18 – Aluminum plate on sash bottom




Figure 19 – Foam backer rod at the end of aluminum frame cover



Figure 20 – Rubber gasket on sill at threshold ends on the exterior



Figure 21 – Foam gaskets used above sash interlock



Figure 22 – Triangle shaped foam gasket on top rail of sash



Figure 23 – Jamb pile weather-stripping




Figure 24 – Sill pile weather-stripping profiles



Figure 25 – Rubber fin seal used on the sill, head, top rail of sash and fixed slab mullion side



Figure 26 – Head track pile weather-stripping



Figure 27 – Head track pile weather-stripping with center fin




Figure 28 – Pile weather-stripping along the head, inserted into black PVC profile.



Figure 29 – Pile weather-stripping along bottom rails of sashes



Figure 30 – Adhesive pile weather-stripping on the aluminum plate at the bottom of sash




Figure 31 – Interlock pile weather-stripping with center fin.



Figure 32 – Vinyl wrapped foam filled weather-stripping on active slab, exterior side.



Figure 33 – Foam weather-stripping on in-active slab locking stile



Figure 34 – Glazing Gaskets




Figure 35 – Roller assembly on the top rail of operable sash



Figure 36 – Aluminum plate inside top rail to secure roller assembly



Figure 37 – Locking assembly

APPENDIX C
Revision Table – 1 Page

<u>Revision Table</u>				
<u>Date</u>	<u>Section</u>	<u>Description</u>	<u>Technician</u>	<u>Reviewer</u>
March 14/17	----	Original Issue Date	----	----