


Hole details - monolythic

**Quantity:** Sets  
**Material:** Grade 304/316 Stainless steel; Please specify  
**Finish:** Machined

@ Doc - Hole in glass Ø19.1 [±0.1] & Csk to suit ferrule bushing NC1-P04  
 @ Pin - Hole in glass/steel min. Ø22.2mm [Ø7.6] / Ø12.7 [Ø0.5]  
 Dimensions millimeter unless otherwise shown  
 Apply locite 243 to all threads during assembly  
 (To increase curing speed, please apply activator 7649)  
 Details are typical and are subject to change to meet project requirement



Drawn	Drawn date
JH	JAN 19-2010
Approved	Approved date
RL	JAN 19-2010
Scale	Rev.
1:2	-

**ASSEMBLY DRAWING**  
**SINGLE POINT DOC & PIN FITTING WITH Ø12mm PIN & COUNTERSUNK INSERT**  
**FORMERLY DP111-NC1**

DWG No	DP6011CM
--------	----------

**stella**  
 Tel (604) 231 5892  
 Fax (604) 231 5893  
 Email info@stellahardware.com

**APPROVAL**

DATE

This drawing is the property of Stella Custom Glass Hardware Inc and may not be copied or reproduced in any way whatsoever without written permission of that company