

ST503TH6S25013 Adjustable Stand-off - Tapered Face

This is one of our best-sellers and for good reason with the first-of-its-kind +/- 6mm [1/4"] in/out adjustability to accommodate uneven mounting surfaces.

This stand-off also uniquely features a shoulder that glass can be rested on during install – allowing installers to rest the glass while they fix the front-mounting face - another labour-saving trick.


In/Out Adjustability

+/- 6mm [1/4"] in/out adjustability

Save install time when the mounting surface is uneven

Front-Mounting

Glass can rest on stand-off's internal shoulder during install



We Give you the Complete Assembly
Part is supplied with all you see here - fibre gaskets and ferrule bushings plus attachment to affix this stand-off to a mounting surface



Adjustable Stand-off contracted (L) and expanded (R)

PRODUCT DATA SHEET



ST503TH6S25013 Adjustable Stand-off (Tapered Face)

Specifications

- Division:
 - 05 73 13: Glazed Decorative Metal Railings
 - 08 88 00: Special Function Glazing
- Materials:
 - Steel: Grade 316 stainless steel
 - Finish: No. 4, 320 grit
 - Gaskets: Material based on high-quality aramid fibers and special functional fillers bonded with NBR, sulfur-free, solvent-free
 - Ferrule Bushing: Acetal delrin
- Mount Type: Vertical mount on top of or below
- Mounting Structure: Steel - thickness 6 to 13mm [1/4" to 1/2"]
- Glass Thickness: 12mm to 21.5mm [1/2" to 7/8"]
- Loading Capability: Lateral load 4kN, Tensile load 4kN, Compressive load 4kN
- LEED Standards:
 - Stainless Steel (primary material) - >45% pre-/95% post- consumer recycled content by weight
- Compliances/Standard: Project specific
- Warranty: 2 year limited warranty* (can be project specific)

Key Details

Typical Applications	<ul style="list-style-type: none">• Guard/balustrades• Partitions/ signage/walls/canopies
Glass Thickness	<ul style="list-style-type: none">• 12mm to 21.5mm [1/2" to 7/8"]
Recommended Diameter Hole In Glass	<ul style="list-style-type: none">• Min - 22.2mm [7/8"]• Rec - 25.4mm [1"]• Max - 28.6mm [1 1/8"]
Key Measurements	<ul style="list-style-type: none">• Cap Face Diameter - 50mm [2"]• Support Bolt - M12 x 45, c/w washer and spring washer
Distance between Glass & Mounting Structure:	<ul style="list-style-type: none">• Min - 48mm [1 3/4"]• Max - 58mm [2 1/4"]
Tool Info	<ul style="list-style-type: none">• Specialized - Stella 4mm Pin Spanner• General - Wrench/Allen Key 1.5mm

A Stella Standard Part "SKU 1187270" Exclusively Distributed via

BRAFASCO **NATIONAL** **BROCKWHITE**
Concrete Accessories

WHITE CAP COMPANIES

www.stellaglasshardware.com